NIRVANADIRECT

INNOVATION SERIES

The Game Changer: designed for direct printing at speed









NIRVANADIRECT

INNOVATION SERIES

Optimum's flagship textile printer configured and optimised, with a patented jumbo-roll feeding system, for reliable high quality direct to fabric printing at high speeds.

This industrial direct to fabric printer utilizes the industry's leading technologies and is available in 2 printing width options: 81" (205cm) and 126" (320cm). This printer includes a 118" (300cm) long industrial fixation unit for direct to fabric application.






Machine Features

- ✓ Smart automatic head cleaning system
- ✓ Separate industrial fixation unit included
- ✓ Integrated vacuum generator with compressed air
- ✓ IGUS energy chains for smooth motion control
- ✓ Aluminium frame and double carriage rail
- ✓ Unwinder/winder dancing tension system (no pinch rollers)
- ✓ Patented industrial jumbo roll feeder with airshaft rolls
- ✓ Safety trigger system for printhead protection
- ✓ Closed design system for safe operation and reduced noise

Printing Features

- ✓ Potential for uninterrupted 24/7 printing operations
- ✓ Low vibrations from strong frame for accurate dotting
- ✓ Up to 1,100lbs (500kg) and 18" (70cm/ 27.5) diameter media rolls
- ✓ Reliable drying at 6,027sqf/h (560sqm/h)
- ✓ Spare-parts and inks inventory at all locations
- ✓ In-house color specialist for customized color profiling





Industrial Printheads 5pl – 73pl Single Channel



PLC Technology German Electronics





Industrial Fixation Unit Not included with printer



Technical Specifications

Default Printhead	Konica Minolta, Kyocera(optional)	Variable Drop		6 pl - 73 pl
Printhead Options	4 / 6 / 8 / 12 / 16 (max 2 rows)	Color Options		4 color - 6 color - 8 color
Ink Compatibility	Disperse / Eco-Pigment / Reactive / Pigment / Acid	Ink Tank System		Open System - 5kg capacity, 20kg external (optional)
Print Width	2.1m & 3.2m	Media Type		Non-Elastic Textiles
Media Drying System	Industrial Drying System	Media Feeding System		Included Feeding System
RIP Software	Neo-Stampa Optimum Digital Special Edition Caldera Textile Pro Enterprise	Max Media Weight		250 kg / 45 cm diameter
		Graphical User Interface (GUI)		ODP Print 3
Power Requirements	Single phase 220VAC /2 5A (for machine) Three phase 380VAC / 32A (for dryer)	Compressed Air		0,6 Mpa @ 2L/min
Printer Dimensions	5500 mm x 2700 mm x 1500 mm		217" x 106" x 59"	
Net Printer Weight	2800 kg		6.172lbs	
Net Machinery Weight	3500 kg		7,716lbs	





Printing made easy



TABLECLOTH



CURTAIN



DECORATIVE PAPER



UPHOLSTERY



SPORTSWEAR



WALLPAPER



FLAGS



BED COVERS



APPAREL

Print on transfer paper, wallpaper as well as non-stretching fabrics with sublimation and pigment technology

NIRVANADIRECT

INNOVATION SERIES







